

Universeal

Locktainer™ 2000 SH High Security Bolt Seal – Technical Specifications



Physical Strength

Pulling load resistance	Over 19 kN
ISO 17712 classification	Grade H: High Security Seal (suitable for C-TPAT operations) Compliant with new ISO FDIS 17712

Material and Dimensions

Barrel	Core	Low Carbon Steel, 18 mm diameter
	Coating	ABS
Pin	Core	Carbon Steel, 8 mm diameter
	Coating	ABS
	Head	18 mm diameter (steel), 22 mm diameter (plastic)
	Sealing length	45,0 mm
Sealed unit total length		80,5 mm

Colours and Printing

Marking zone	25 mm x 16 mm
Printing type	Laser
Printing specifications	First line: Customer ID , Second line: Numbering
Customer ID	Standard: Alphanumeric , Optional: B&W or colored graphic logo
Numbering	Alphanumeric or Barcode , double numbering on pin head
Standard colours	Red, Green, Blue, Light blue, Dark blue, Orange, Yellow, White, Grey

Packaging

Bundle	10 pieces in individual blister pack
Seals per carton	250 pieces
Carton dimensions	378 mm x 245 mm x 136 mm
Carton weight	Approx. 13,0 kg

Note : Universeal reserves the right to change specifications without prior notice.

January 2011

