



Plain Cable Ties

- ✓ Manufactured in Nylon 6/6 material
- ✓ Available in black, natural & various colours
- ✓ Operating Temperature: -40C to +85C
- ✓ ISO 9001:2008 standard
- ✓ RoHs compliant
- ✓ UL-94 V-2 approved

Miniature Cable ties: 2.5mm width

Approx. Sizing	Colour	Code	Pack Qty.	Max Bundle Diam. (mm)	Tensile Strength (kgs)
100x2.5 mm	Black / natural	UVZIP-10025-B/N	100	18	8.1
100x2.5mm	R/Y/BL/G/O/P	UVZIP-10025-R/Y/BL/G/O/P	100	18	8.1
160x2.5 mm	Black / natural	UVZIP-16025-B/N	100	40	8.1
200x2.5mm	Black / natural	UVZIP-20025-B/N	100	50	8.1
200x2.5 mm	R/B/G	UVZIP-20025-R/B/G	100	50	14
300x2.5mm	Black / natural	UVZIP-30028-B/N	100	50	14



R: Red /Y: Yellow /BL: Blue /G: Green /O: Orange /P: Purple /S: Silver

Intermediate Cable ties: 3.6 mm width

Approx. Sizing	Colour	Code	Pack Qty.	Max Bundle Diam. (mm)	Tensile Strength (kgs)
140x3.6mm	Black / natural	UVZIP-14036-B/N	100	33	18.2
140x3.6mm	R/Y/BL/G/S	UVZIP-14036-R/Y/BL/G/S	100	33	18.2
200x3.6 mm	Black / natural	UVZIP-20036-B/N	100	50	18.2
200x3.6mm	R/Y/BL/G	UVZIP-20036-R/Y/BL/G	100	50	18.2
300x3.6 mm	Black / natural	UVZIP-30036-B/N	100	76	18.2
300x3.6mm	Blue	UVZIP-30036-BL	100	76	18.2
370x3.6mm	Black / natural	UVZIP-37036-B/N	100	102	18.2



R: Red /Y: Yellow /BL: Blue /G: Green /O: Orange /P: Purple /S: Silver

Standard Cable ties: 4.8mm width

Approx. Sizing	Colour	Code	Pack Qty.	Max Bundle Diam. (mm)	Tensile Strength (kgs)
160x4.8mm	Black/natural	UVZIP-16048-B/N	100	38	22.2
200x4.8mm	Black/natural	UVZIP-20048-B/N	100	50	22.2
200x4.8mm	R/Y/BL/G/O/P/S	UVZIP-20048- R/Y/BL/G/O/P/S	100	50	22.2
300x4.8mm	Black/natural	UVZIP-30048-B/N	100	76	22.2
300x4.8mm	R/Y/BL/G/O/P/S	UVZIP-30048- R/Y/BL/G/O/P/S	100	76	22.2
370x4.8mm	Black/natural	UVZIP-37048-B/N	100	102	22.2
370x4.8mm	R/Y/BL/O/S	UVZIP-37048- R/Y/BL/O/S	100	102	22.2
430x4.8mm	Black/natural	UVZIP-43048-B/N	100	114	22.2
530x4.8mm	Black/natural	UVZIP-53048-B/N	100	140	22.2



R: Red /Y: Yellow /BL: Blue /G: Green /O: Orange /P: Purple /S: Silver

Medium-Duty Cable ties: 7.6mm width

Approx. Sizing	Colour	Code	Pack Qty.	Max Bundle Diam. (mm)	Tensile Strength (kgs)
200x7.6mm	Black/natural	UVZIP-20076-B/N	100	50	54.5
300x7.6 mm	Black	UVZIP-30076-B	100	76	54.5
370x7.6mm	Black/natural	UVZIP-37076-B/N	100	102	54.5
450x7.6 mm	Black/natural	UVZIP-45076-B/N	100	127	54.5
530x7.6mm	Black/natural	UVZIP-53076-B/N	100	140	54.5
610x7.6mm	Natural	UVZIP-61076-N	100	185	54.5

**Heavy-duty Cable ties: 9.0mm width**

Approx. Sizing	Colour	Code	Pack Qty.	Max Bundle Diam. (mm)	Tensile Strength (kgs)
430x9mm	Black/natural	UVZIP-4309-B/N	100	110	79.4
530x9mm	Black/natural	UVZIP-5309-B/N	100	140	79.4
610x9mm	Black/natural	UVZIP-6109-B/N	100	185	79.4
710x9mm	Black/natural	UVZIP-7109-B/N	100	190	79.4
810x9mm	Natural	UVZIP-8109-N	100	240	79.4
940x9mm	Black	UVZIP-9409-B	100	280	79.4

**Extra Heavy-Duty Cable ties: 12.7mm width**

Approx. Sizing	Colour	Code	Pack Qty.	Max Bundle Diam. (mm)	Tensile Strength (kgs)
430x12.7mm	Black/natural	UVZIP-430127-B/N	100	125	113.5
580x12.7mm	Black/natural	UVZIP-580127-B/N	100	152	113.5
730x12.7mm	Natural	UVZIP-730127-N	100	206	113.5
1030x12.7mm	Black	UVZIP-1030127-B/N	100	307	113.5

**STORAGE INFORMATION**

Universeal UK cable ties and related accessories are made from high quality Dupont nylon 66 resin.

Nylon both absorbs and releases moisture – for optimal performance the cable ties will need to contain 2-3% moisture. To ensure maximal performance, cable ties should be kept in accordance with the following storage conditions:

- ✓ The ideal storage climate for cable ties is between 15-20°C;
- ✓ Do not store or use cable ties in direct sunlight;
- ✓ Always keep the cable ties in sealed polyethylene bag provided – cable ties should be used shortly after opening the package;
- ✓ Do not store the cable ties next to warm objects, such as radiators or fan heaters



Universeal UK, 9 Portal Business Park, Tarporley, Cheshire, CW6 9DL

Tel: 00 44 (0)1829 760000 Fax: 00 44 (0)1829 760011

sales@universeal.co.uk

www.universeal.co.uk