

## Specification Sheet

### UVWR – Sealing Wire

Sealing wire is suitable for use with sealing ferrules, lead seals, Twister seals and other security seals. Available in diameters from 0.5mm-1.6mm, in galvanised steel, 304/316 stainless steel and nylon/copper materials.

Multiple configurations available, including 2-line spiral wire and 7-strand twisted sealing wire. Optional PVC coating available. Supplied in reel format or pre-cut wire lengths.



#### Applications

Electrical, gas and utility meter sealing in conjunction with security seals

#### Material

Galvanised steel, stainless steel, copper/nylon material options









#### Customisation Options

Material options, custom spooling and pre-cut lengths, PVC coating

#### Packaging

Supplied on spools or in pre-cut lengths (MOQ may apply).

Commonly available wire configuration formats shown below

Type	Construction	Code	Material	Specification	Availability
7-Line Stranded Wire 		UVWR-151	Galvanised Steel	0.66mm diameter (7 x 0.23mm stranded)	Customised
		UVWR-153	Stainless Steel	0.66mm diameter (7 x 0.23mm stranded)	Customised
		UVWR-093GAL7S	Galvanised Steel	0.93mm diameter (7 x 0.32mm stranded)	15cm / 20cm pre-cut
7-Line Stranded Wire + PVC Coating 		UVWR-152	Galvanised + PVC	0.9mm diameter (7 x 0.23mm stranded + coating)	Customised
		UVWR-154	Stainless + PVC	0.9mm diameter (7 x 0.23mm stranded + coating)	Customised
2-Line Spiral Wire 		UVWR-GLW85	Galvanised Steel	1.05mm diameter (0.45mm core + 0.3mm spiral)	200metre spools
		UVWR-GLW75	Galvanised Steel	1.6mm diameter (0.7mm core + 0.45mm spiral)	88metre spools
		UVWR-SS304L	Stainless Steel	1.1mm diameter (0.5mm core + 0.3mm spiral)	200metre spools
		UVWR-155	Galvanised Steel	0.9mm diameter (0.45mm core + 0.25mm spiral)	Customised
		UVWR-156	Stainless Steel	0.9mm diameter (0.45mm core + 0.25mm spiral)	Customised
Nylon/Copper Spiral Wire 		UVWR-157	Nylon/Copper	1mm diameter. (0.50mm core + 0.30mm spiral)	Customised