

# Universeal

## flexiGrip™ 250 M “nano” Security Cable Seal – Technical Specifications



### Physical Strength

Pulling load resistance	600 kg
-------------------------	--------

### Material and Dimensions

Body	Aluminium alloy
L x H x T	26 mm x 22 mm x 6 mm
Cable	Non preformed galvanized aircraft cable
Diameter	2,5 mm
Usable length	250 mm
Mechanism	Zinc alloy
Flat spring	Spring steel (Heat treated)
Roller	Steel (Heat treated)

### Colours and Printing

Marking zone	26 mm x 17 mm
Printing type	Laser
Printing specifications	First line: <b>Customer ID</b> , Second line: <b>Numbering</b>
Customer ID	Standard: <b>Alphanumeric</b> , Optional: <b>B&amp;W graphic logo</b>
Numbering	<b>Alphanumeric or Barcode</b>
Standard colours (anodized)	<b>Red, Green, Blue, Dark Blue, Yellow, Orange, Grey, Black</b>

### Packaging

Bundle	<b>10 pieces sequentially attached with rubber band</b>
Seals per carton	<b>500 pieces in 50 bundles</b>
Carton dimensions	<b>310 mm x 280 mm x 130 mm</b>
Carton weight	<b>Approx. 9,9 kg</b>

*Note : Universeal reserves the right to change specifications without prior notice.*

January 2011

